

# **TECHNICAL CERTIFICATE**

Tent-sauna, fisherman tent, winter tent

### **MORZH MAX**

www.morzh.eu



# **Description and purpose**

A mobile tent sauna is universal and can be used as a winter tent for living, fishing, hunting and as a mobile tent sauna. MORZH Max has enlarged dimensions and removable internal partition to make a comfortable vestibule for relaxing, changing clothes, storing things or creating a large heated tent. The tent is universal and it supports the installation of 2 stoves.

# **Specifications**

Parameters	MORZH Max
Length, m	2,96
Width, m	2,3
Sidewall height, m	1,72
Center height, m	1,97
Effective area, m <sup>2</sup>	6,9
Tent weight, kg	17,7
Number of berths	4
Kind, dimensions of package	1 bag with dimensions 65 * 45 * 45 cm

## **Completeness**

- 1. Frame arc 4 pcs.
- 2. Longitudinal stringers 3 pcs.
- 3. Tent awning 1 pc.
- 4. Shipping bag 1 pc.
- 5. Frame pouch 1 pc.
- 6. A set of wind braces 1 pc.
- 7. ZIP (piece of cloth) 1 pc.
- 8. Screw 10 pcs.
- 9. Technical certificate 1 pc.
- 10. Hanging net for storage and drying things (weight limit: no more than 5 kg)1 pc.

The awning of the tent is made of a three-layer quilted cloth consisting of Oxford fabric 240 / heater  $80 \sim 100$  g / m2 / Taffeta 210.

The top of the awning is made of Oxford 240 polyester fabric with water-repellent impregnation. The inner awning is made of light synthetic Taffeta fabric. Between 2 layers of external and internal awnings there is a heater made of synthetic fabric with a density of 80 g / m2. They are quilted with a thermal stitch.

In the tent there are 2 cuts for the chimney made of stainless steel and special fiberglass with silicone double sided coating.

#### **Functional equipment**

The entrance is equipped with zippers for easy and quick access to the tent. On the sides there are windows made of thermopolyurethane film. The tent includes pockets and a net for storing and drying things.

The chimney section is made of stainless steel and special fiberglass with a silicone double sided coating, designed for stove with 90 mm chimney diameter. To install stove with a smaller diameter of the chimney, it is recommended to use an adapter ring. There is a ventilation window for the air to reach the stove. The window has a mosquito net.

#### Assembly order

The assembly of the tent should begin with the installation of the frame arcs into the pockets, which are located at the corners of the tent. After installing the frames in pockets, you need to close the zipper to hold the frame inside. After the assembly, you should cut the supplied guy rope into pieces and be sure to install all the wind guys! They are needed to keep the tent firmly in the wind, and also so that the stove does not touch the tent wall. Before installing the stove, be sure to open the valve closing the chimney section. The valve opens downward and is secured with a Velcro tape on the corner brace.

#### **Precautionary measures**

- Fix the tent carefully on the ground to prevent it from tipping over.
- Do not use a camping stove and other heating devices in a tent when the wind is more than 10 m / s.
- It is not recommended to install the tent close to the crowns of trees or other tents.
- Do not allow intoxicated persons or young children to use.
- Do not use gas or flammable substances to light the stove inside the tent.

#### Terms of use

The product can be used in temperature modes from -40C to +40C. The installation of all wind braces required. Be sure to observe all safety precautions when installing the stove. Do not install the stove close to the wall of the tent. Use stoves with a spark arrestor. Clean the chimney from soot during prolonged living and use. If there is a warm floor, it is not necessary in sauna mode.

#### Storage and transportation

The tent should be kept dry. It is recommended to dry the tent after each use. Shake out the sand and leaves from the tent after each use. Clean the tent from dirt with a soft cloth or sponge and soap. Do not use strong chemical cleaners. Never wash the tent in a washing machine and do not iron it. When there are tears, try to glue or sew them as soon as possible. Always try to fold the awning with polyurethane coating inside. Arcs and pegs should be stored in special cases, otherwise they can damage the tent.

Warranty Card	
Technical control department date «»20 ı	Γ.
Name:	_
Color :	
Date of sale: «»20 г.	
Buyer's signature/	

#### Manufactured by order:

New Solution LLC, 620043, Cherklasskaya str. 9, Sverdlovsk Region Ekaterinburg, Russia TIN 6658182671, CRR 665801001 +7 (343) 386-19-75

\*\* (343) 360-19-73

